User friendly micro scrubber/dryer perfect for cleaning in narrow areas

With this compact micro scrubber/dryer you can easily clean the floors in narrow areas.

The AS380/15 is easy to use and with handles on the side of the water tank makes it highly user-friendly. The foldable handles makes it easy to transport and storage the machine.

Extremely compact machine that makes it easy to manoeuvre and transport.

You will find it ideally suitable for daily indoor scrubbing and drying in light to medium areas such as offices, hotels, hospitals, schools, smaller supermarkets and other retail outlet.

- · Ergonomic, adjustable and foldable handle
- · Extremely compact
- · Easy to manoeuvre, transport and storage
- · Easy to use and service
- · Easy to clean, refill and empty
- Suitable for application in narrow area
- · Rotationally moulded tank
- · Robust handle lock
- Two tanks system
- Battery and Cable versions EU and UK versions.



Picture shown may not represent model quoted

The AS380/15 is a compact and user-friendlymicro scrubber/dryer perfect forcleaning in narrow areas

Standard equipment

	Included accessories	Ref. no.	Min. required	AS380/15B- EU 15 SCRUBBER 24V 50/60HZ	AS380/15B- UK 15 SCRUBBER 24V 50/60HZ	AS380/15C- EU 15 230-240V 50/60HZ		
and the same	Battery and Charger							
	KIT CHARGER 24VDC 50-60HZ	VF89023UK	1		•			
E 11	KIT CHARGER 24VDC 50-60HZ	VF89023EU	1	•				
	Viper Accessory							
	BLADE SQUEEGEE FRONT	VF89807	0	•	•	•		
	BLADE SQUEEGEE REAR	VF89808	0	•	•	•		
	BRUSH 15INCH PLASTIC	VF89830	0	•	•	•		
	KIT SQUEEGEE ALUMINUM	VF89821	0	•	•	•		

Standard equipment

	Included accessories	Ref. no.	Min. required	AS380/15C- UK 15 230-240V 50/60HZ	AS380/15B- CN 15 SCRUBBER 24V 50/60HZ	AS380/15C- CN 15 220V 50/60HZ		
and the latest the lat	Battery and Charger							
	KIT CHARGER 24VDC 50-60HZ	VF89023UK	1					
	KIT CHARGER 24VDC 50-60HZ	VF89023EU	1					
	Viper Accessory							
	BLADE SQUEEGEE FRONT	VF89807	0	•	•	•		
	BLADE SQUEEGEE REAR	VF89808	0	•	•	•		



User friendly micro scrubber/dryer perfect for cleaning in narrow areas

Included accessories	Ref. no.	Min. required	AS380/15C- UK 15 230-240V 50/60HZ	AS380/15B- CN 15 SCRUBBER 24V 50/60HZ	AS380/15C- CN 15 220V 50/60HZ
BRUSH 15INCH PLASTIC	VF89830	0	•	•	•
KIT SQUEEGEE ALUMINUM	VF89821	0	•	•	•

_			
•	Standard	equipn	nent

	Included accessories	Ref. no.	Min. required	AS380/15B-TR SCRUBBER 24V 50/60HZ	AS380/15C- TR SCRUBBER 230-240V 50/60HZ
and the latest the lat	Battery and Charger				
	KIT CHARGER 24VDC 50-60HZ	VF89023UK	1		
B # 1	KIT CHARGER 24VDC 50-60HZ	VF89023EU	1	•	
	Viper Accessory				
	BLADE SQUEEGEE FRONT	VF89807	0	•	•
	BLADE SQUEEGEE REAR	VF89808	0	•	•
	BRUSH 15INCH PLASTIC	VF89830	0	•	•
	KIT SQUEEGEE ALUMINUM	VF89821	0	•	•

Model	AS380/15B-EU 15 SCRUBBER 24V 50/60HZ	AS380/15B-UK 15 SCRUBBER 24V 50/60HZ	AS380/15C-EU 15 230-240V 50/60HZ
Ref. no.	50000199	50000200	50000201
PRODUCT FEATURES			
Compact design	•	•	•
Adjustable handle	•	•	•
Model	AS380/15C-UK 15 230-240V 50/60HZ	AS380/15B-CN 15 SCRUBBER 24V 50/60HZ	AS380/15C-CN 15 220V 50/60HZ
Ref. no.	50000202	50000205	50000206
PRODUCT FEATURES			
Compact design	•	•	
Adjustable handle	•	•	
Model		AS380/15B-TR SCRUBBER 24V 50/60HZ	AS380/15C-TR SCRUBBER 230-240V 50/60HZ
Ref. no.		50000211	50000212
PRODUCT FEATURES			



Compact design

Adjustable handle

User friendly micro scrubber/dryer perfect for cleaning in narrow areas

Energy Label Compressure level (d8/A) 65 65 69 Cable length (m)/ plug type 65 65 69 Waculum motor power (W) 250 250 250 Battery type 2X12V/33AH/20H 2X12V/33AH/20H 6 Vacuum (mH H2O) 800 800 800 Productivity rate (mPh) 750 15 15 Productivity rate (mPh) 15 15 15 Productivity rate (mPh) 15 15 15 Recovery tank (I) 15 15 15 Squeepe width (mm) 480 490 490 Push (PM) 150 150 140 Push speed (RPM) 150 150 140 Bettery compartment size (LxWell-) (mm) 196x130x175 196x13x175 - Gross weight (gwy) (lig) 6 6 4 Departing weight (kgy) 6 6 4 Tempt Label 6 6 6 Extractional Specifications 6 6 <th>Technical specifications</th> <th>AS380/15B-EU 15 SCRUBBER 24V 50/60HZ</th> <th>AS380/15B-UK 15 SCRUBBER 24V 50/60HZ</th> <th>AS380/15C-EU 15 230-240V 50/60HZ</th>	Technical specifications	AS380/15B-EU 15 SCRUBBER 24V 50/60HZ	AS380/15B-UK 15 SCRUBBER 24V 50/60HZ	AS380/15C-EU 15 230-240V 50/60HZ
Cabbe length (mi) pig type - - 15EU Brush motor (W) 250 250 250 Vacuum motor power (W) 300 300 300 Battery type 2X12V/33Ah/20H 2X12V/33Ah/20H - Vacuum (mm H2O) 800 800 800 Productivity rate (m/h) 750 750 750 Solution tank (I) 15 15 15 Recovery tank (I) 15 16 15 Squeegee width (mm) 380 380 380 Brush speed (RPM) 150 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LWWxH) (min) 196x130x175 196x130x175 - Gross weight (gww) (kg) 65 65 44 Operating weight (kg) 60 60 40 Technical specifications 68 69 88 69 Energy Label 5 5 5 88 69 6	Energy Label			
Brush motor (W) 250 250 250 Vacuum motor power (W) 300 300 300 Battery type 2X12V/33Ah/20H 2X12V/33Ah/20H - Vacuum (mm HZO) 800 800 800 Productivity rate (m²h) 750 750 750 15 Solution tank (I) 15 15 15 15 Recovery tank (I) 15 15 15 15 Squeegee width (mm) 490 490 490 490 Brush speed (RPM) 150 150 380 380 Brush speed (RPM) 150 150 780×415x90 780×415x90 Battery compartment size (x,xWxH) (mm) 780×415x94 780×415x90 780×415x90 Battery compartment size (x,xWxH) (mm) 198x130x175 198x130x175 - Gross weight (gwy) (kig) 65 65 65 44 Operating weight (kg) 60 60 40 Energy Label 2 2 250 250 <td< td=""><td>Sound pressure level (dB(A))</td><td>65</td><td>65</td><td>69</td></td<>	Sound pressure level (dB(A))	65	65	69
Vacuum motor power (W) 300 300 300 Battery type 2X12V/33Ah/20H 2X12V/33Ah/20H - Vacuum (mm H2O) 800 800 800 Productivity rate (m²/h) 750 750 750 Solution tank (I) 15 15 15 15 Recovery tank (I) 15 15 15 15 Squeegee width (mm) 490 490 490 490 Brush pad diameter (mm) 380 380 380 380 Brush peed (RPM) 150 150 140 <td< td=""><td>Cable length (m)/ plug type</td><td>-</td><td>-</td><td>15/EU</td></td<>	Cable length (m)/ plug type	-	-	15/EU
Battery type 2X12V/33AN/20H 2X12V/33AN/20H Calcal Control Co	Brush motor (W)	250	250	250
Vacuum (mm H2O) 800 800 800 Productivity rate (m²/h) 750 750 750 Solution tank (i) 15 15 15 Recovery tank (i) 15 15 15 Squeegee width (mm) 490 490 490 Brush spaed (RPM) 150 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) 196x130x175 196x130x175 - Gross weight (gww) (kg) 65 65 44 Operating weight (kg) 66 65 44 Operating weight (kg) 60 60 40 Technical specifications AS380/15C-UK 15 250x15EC-UK 5 220x150/60Hz Energy Label 66 66 44 Sound pressure level (dB(A)) 69 68 69 Cable length (m/) / plug type 15/UK 5 15/UK Srush motor (W) 30 30 300 Vacuum motor power (W)	Vacuum motor power (W)	300	300	300
Productivity rate (m³/h) 750 750 750 Solution tank (l) 15 15 15 Recovery tank (l) 15 15 15 Squeegee width (rmn) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 150 150 140 Length x width x height (mm) 780x415x990 780x415x990 780x415x990 Battery compartment size (LxWxH) (mm) 196x130x175 196x130x175 - Gross weight (gww) (kg) 65 65 44 Operating weight (kg) 66 66 40 Technical specifications AS380/15C-URLS 250 250 Technical specifications 66 66 44 Operating weight (kg) 66 66 40 Technical specifications 68 69 66 69 Cell productivity (gww) (kg) 60 60 60 60 60 60 60 60 60 60 60	Battery type	2X12V/33Ah/20H	2X12V/33Ah/20H	-
Solution tank (I) 15 15 15 Recovery tank (I) 15 15 15 Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 150 150 140 Length x width x height (mm) 780x415x590 780x415x590 <t< td=""><td>Vacuum (mm H2O)</td><td>800</td><td>800</td><td>800</td></t<>	Vacuum (mm H2O)	800	800	800
Recovery tank (I) 15 15 15 Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 150 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) 196x130x175 196x130x175 - Gross weight (gwy) (kg) 65 65 65 44 Operating weight (kg) 60 60 40 Technical specifications AS380/15C-UK 15 230-240V 50/60Hz AS380/15C-UK 15 250/00Hz AS380/15C-UK 15 220V 50/60Hz AS380/15C-UK 15 200/00Hz AS380/15C-UK 15 	Productivity rate (m²/h)	750	750	750
Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 150 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LXWXH) (mm) 196x130x175 196x130x175 - Gross weight (gwv) (kg) 65 65 44 Operating weight (kg) 60 60 40 Technical specifications AS380/15C-UK 15 AS380/15B-C 15 AS380/15C-CN 15 Energy Label Technical specifications 69 68 69 Cable length (m/) plug type 15/UK - 15/UK Brush motor (W) 250 250 250 Vacuum (mm H2O) 800 800 800 Productivity rate (m*/h) 750 750 750 Solution tank (l) 15 15 15 Recovery tank (l) 15 15 15 Squeegee width (mm) 490 490 490	Solution tank (I)	15	15	15
Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 150 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) 196x130x175 196x130x175 - Gross weight (gwy) (kg) 65 65 44 Operating weight (kg) 60 60 40 Technical specifications AS380/15C-CN 15 28380/15C-CN 15 28380/15C-CN 15 220x20x50/60Hz Energy Label Technical pressure level (dB(A)) 69 68 69 Cable length (m/) plug type 157UK - 157UK Brush motor (W) 250 250 250 Vacuum motor power (W) 300 300 300 Battery type - 2X12V/33Ah/20H - Vacuum (mm H2O) 800 80 80 Productivity rate (m³/h) 750 750 750 Solution tank (l) 15 15 15 Eccovery tank (l) 380 <td< td=""><td>Recovery tank (I)</td><td>15</td><td>15</td><td>15</td></td<>	Recovery tank (I)	15	15	15
Brush speed (RPM) 150 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) 196x130x175 196x130x175 - Gross weight (gww) (kg) 65 65 44 Operating weight (kg) 60 60 40 Technical specifications AS380/15C-UX15 SCRUBBER 24V AS380/15C-CN 15 220V 50/60HZ Energy Label B 68 69 68 69 Cable length (m/) plug type 15/UK - 15/UK Brush motor (W) 250 250 250 Vacuum motor power (W) 300 300 300 Battery type - 2X12V/33Ah/20H - Vacuum (mm H2O) 800 80 80 Productivity rate (m²/h) 750 750 750 Solution tank (l) 15 15 15 Ecovery tank (l) 15 15 15 Squeegee width (mm) 490 490 490	Squeegee width (mm)	490	490	490
Length x width x height (mm) 780x415x590 780x4	Brush/pad diameter (mm)	380	380	380
Battery compartment size (LxWxH) (mm) 196x130x175 196x130x175 - Gross weight (gww) (kg) 65 65 44 Operating weight (kg) 60 60 40 Technical specifications AS380/15C-UK 15 200-V50/60HZ AS380/15E-CN 15 50/60HZ AS380/15C-CN 15 AS380/15C-CN 15 AS380/15C-CN 15 AS380/15C-CN 15 AS380/15C-CN 15 AS080/15C-CN 15	Brush speed (RPM)	150	150	140
Gross weight (gww) (kg) 65 65 44 Operating weight (kg) 60 60 40 Technical specifications AS380/15C-UK 15 200-V 50/60HZ AS380/15E-UK 15 SCRUBBER 24V S0/60HZ AS380/15C-UN 15 SCRUBBER 24V S0/60HZ Energy Label From 15 SCRUBBER 24V S0/60HZ AS380/15C-UK 15 SCRUBBER 24V S0/60HZ AS380/15C-UK 15 SCRUBBER 24V S0/60HZ Sound pressure level (dB(A)) 69 68 69 Cable length (m)/ plug type 15/UK - 15/UK Brush motor (W) 250 250 250 250 Vacuum motor power (W) 300 300 300 300 Battery type - 2X12V/33Ah/20H - - Vacuum (mm H2O) 800 800 800 800 Productivity rate (m²/h) 750 750 750 750 Solution tank (I) 15 15 15 15 Recovery tank (I) 380 380 380 380 Brush/pad diameter (mm) 380 380 380 380 <t< td=""><td>Length x width x height (mm)</td><td>780x415x590</td><td>780x415x590</td><td>780x415x590</td></t<>	Length x width x height (mm)	780x415x590	780x415x590	780x415x590
Operating weight (kg) 60 40 Technical specifications AS380/15C-UK 15 230-240V 50/60HZ AS380/15B-CN 15 SCRUBBER 24V 50/60HZ AS380/15C-CN 15 SCRUBBER 24V 50/60HZ Energy Label SUBJECT 200 SCRUBBER 24V 50/60HZ SCRUBBER 24V 50/60HZ SCRUBBER 24V 50/60HZ Sound pressure level (dB(A)) 69 68 69 Cable length (m)/ plug type 15/UK - 15/UK Brush motor (W) 250 250 250 Vacuum motor power (W) 300 300 300 Battery type - 2X12V/33Ah/20H - Vacuum (mm H2O) 800 800 800 Productivity rate (m²/h) 750 750 750 Solution tank (I) 15 15 15 Recovery tank (I) 15 15 15 Squeegee width (mm) 490 490 490 Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) 780x415x590 780x415x590	Battery compartment size (LxWxH) (mm)	196x130x175	196x130x175	-
Technical specifications AS380/15C-UK 15 230-240V 50/60HZ AS380/15C-CN 15 220V 50/60HZ AS380/15C-CN 15 220V 50/60HZ Energy Label Freely Bell of the properties of the propert	Gross weight (gvw) (kg)	65	65	44
Technical specifications 230-240V 50/60HZ SCRUBBER 24V 50/60HZ ASSENCY 50/60HZ Energy Label Sound pressure level (dB(A)) 69 68 69 Cable length (m)/ plug type 15/UK - 15/UK Brush motor (W) 250 250 250 Vacuum motor power (W) 300 300 300 Battery type - 2X12V/33Ah/20H - Vacuum (mm H2O) 800 800 800 Productivity rate (m²/h) 750 750 750 Solution tank (I) 15 15 15 Recovery tank (I) 15 15 15 Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - - Gross weight (gww) (kg) 44 65 <t< td=""><td>Operating weight (kg)</td><td>60</td><td>60</td><td>40</td></t<>	Operating weight (kg)	60	60	40
Sound pressure level (dB(A)) 69 68 69 Cable length (m)/ plug type 15/UK - 15/UK Brush motor (W) 250 250 250 Vacuum motor power (W) 300 300 300 Battery type - 2X12V/33Ah/20H - Vacuum (mm H2O) 800 800 800 Productivity rate (m²/h) 750 750 750 Solution tank (I) 15 15 15 Recovery tank (I) 15 15 15 Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - - Gross weight (gyw) (kg) 44 65 44				
Cable length (m)/ plug type 15/UK - 15/UK Brush motor (W) 250 250 250 Vacuum motor power (W) 300 300 300 Battery type - 2X12V/33Ah/20H - Vacuum (mm H2O) 800 800 800 Productivity rate (m²/h) 750 750 750 Solution tank (I) 15 15 15 Recovery tank (I) 15 15 15 Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - Gross weight (gvw) (kg) 44 65 44	Technical specifications		SCRUBBER 24V	
Brush motor (W) 250 250 250 Vacuum motor power (W) 300 300 300 Battery type - 2X12V/33Ah/20H - Vacuum (mm H2O) 800 800 800 Productivity rate (m²/h) 750 750 750 Solution tank (I) 15 15 15 Recovery tank (I) 15 15 15 Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - Gross weight (gvw) (kg) 44 65 44			SCRUBBER 24V	
Vacuum motor power (W) 300 300 300 Battery type - 2X12V/33Ah/20H - Vacuum (mm H2O) 800 800 800 Productivity rate (m²/h) 750 750 750 Solution tank (I) 15 15 15 Recovery tank (I) 15 15 15 Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - Gross weight (gvw) (kg) 44 65 44	Energy Label	230-240V 50/60HZ	SCRUBBER 24V 50/60HZ	220V 50/60HZ
Battery type - 2X12V/33Ah/20H - Vacuum (mm H2O) 800 800 800 Productivity rate (m²/h) 750 750 750 Solution tank (l) 15 15 15 Recovery tank (l) 15 15 15 Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - Gross weight (gvw) (kg) 44 65 44	Energy Label Sound pressure level (dB(A))	230-240V 50/60HZ 69	SCRUBBER 24V 50/60HZ	220V 50/60HZ 69
Vacuum (mm H2O) 800 800 800 Productivity rate (m²/h) 750 750 750 Solution tank (I) 15 15 15 Recovery tank (I) 15 15 15 Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - Gross weight (gvw) (kg) 44 65 44	Energy Label Sound pressure level (dB(A)) Cable length (m)/ plug type	230-240V 50/60HZ 69 15/UK	SCRUBBER 24V 50/60HZ 68	220V 50/60HZ 69 15/UK
Productivity rate (m²/h) 750 750 750 Solution tank (I) 15 15 15 Recovery tank (I) 15 15 15 Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - Gross weight (gvw) (kg) 44 65 44	Energy Label Sound pressure level (dB(A)) Cable length (m)/ plug type Brush motor (W)	230-240V 50/60HZ 69 15/UK 250	SCRUBBER 24V 50/60HZ 68 - 250	220V 50/60HZ 69 15/UK 250
Solution tank (I) 15 15 15 Recovery tank (I) 15 15 15 Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - Gross weight (gvw) (kg) 44 65 44	Energy Label Sound pressure level (dB(A)) Cable length (m)/ plug type Brush motor (W) Vacuum motor power (W)	230-240V 50/60HZ 69 15/UK 250 300	68 - 250 300	220V 50/60HZ 69 15/UK 250 300
Recovery tank (I) 15 15 15 Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - Gross weight (gvw) (kg) 44 65 44	Energy Label Sound pressure level (dB(A)) Cable length (m)/ plug type Brush motor (W) Vacuum motor power (W) Battery type	230-240V 50/60HZ 69 15/UK 250 300 -	68 - 250 300 2X12V/33Ah/20H	220V 50/60HZ 69 15/UK 250 300 -
Squeegee width (mm) 490 490 490 Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - Gross weight (gvw) (kg) 44 65 44	Energy Label Sound pressure level (dB(A)) Cable length (m)/ plug type Brush motor (W) Vacuum motor power (W) Battery type Vacuum (mm H2O)	230-240V 50/60HZ 69 15/UK 250 300 - 800	68 - 250 300 2X12V/33Ah/20H 800	220V 50/60HZ 69 15/UK 250 300 - 800
Brush/pad diameter (mm) 380 380 380 Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - Gross weight (gvw) (kg) 44 65 44	Energy Label Sound pressure level (dB(A)) Cable length (m)/ plug type Brush motor (W) Vacuum motor power (W) Battery type Vacuum (mm H2O) Productivity rate (m²/h)	230-240V 50/60HZ 69 15/UK 250 300 - 800 750	68 - 250 300 2X12V/33Ah/20H 800 750	220V 50/60HZ 69 15/UK 250 300 - 800 750
Brush speed (RPM) 140 150 140 Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - Gross weight (gvw) (kg) 44 65 44	Energy Label Sound pressure level (dB(A)) Cable length (m)/ plug type Brush motor (W) Vacuum motor power (W) Battery type Vacuum (mm H2O) Productivity rate (m²/h) Solution tank (I)	230-240V 50/60HZ 69 15/UK 250 300 - 800 750 15	68 - 250 300 2X12V/33Ah/20H 800 750	220V 50/60HZ 69 15/UK 250 300 - 800 750 15
Length x width x height (mm) 780x415x590 780x415x590 780x415x590 Battery compartment size (LxWxH) (mm) - 196x130x175 - Gross weight (gvw) (kg) 44 65 44	Energy Label Sound pressure level (dB(A)) Cable length (m)/ plug type Brush motor (W) Vacuum motor power (W) Battery type Vacuum (mm H2O) Productivity rate (m²/h) Solution tank (I) Recovery tank (I)	69 15/UK 250 300 - 800 750 15	68 - 250 300 2X12V/33Ah/20H 800 750 15 15	220V 50/60HZ 69 15/UK 250 300 - 800 750 15
Battery compartment size (LxWxH) (mm) - 196x130x175 - Gross weight (gvw) (kg) 44 65 44	Energy Label Sound pressure level (dB(A)) Cable length (m)/ plug type Brush motor (W) Vacuum motor power (W) Battery type Vacuum (mm H2O) Productivity rate (m²/h) Solution tank (I) Recovery tank (I) Squeegee width (mm)	69 15/UK 250 300 - 800 750 15 15 490	68 - 250 300 2X12V/33Ah/20H 800 750 15 15 490	220V 50/60HZ 69 15/UK 250 300 - 800 750 15 15 490
Gross weight (gvw) (kg) 44 65 44	Energy Label Sound pressure level (dB(A)) Cable length (m)/ plug type Brush motor (W) Vacuum motor power (W) Battery type Vacuum (mm H2O) Productivity rate (m²/h) Solution tank (I) Recovery tank (I) Squeegee width (mm) Brush/pad diameter (mm)	69 15/UK 250 300 - 800 750 15 15 490 380	68 - 250 300 2X12V/33Ah/20H 800 750 15 15 490 380	220V 50/60HZ 69 15/UK 250 300 - 800 750 15 15 490 380
	Energy Label Sound pressure level (dB(A)) Cable length (m)/ plug type Brush motor (W) Vacuum motor power (W) Battery type Vacuum (mm H2O) Productivity rate (m²/h) Solution tank (I) Recovery tank (I) Squeegee width (mm) Brush/pad diameter (mm) Brush speed (RPM)	69 15/UK 250 300 - 800 750 15 15 490 380 140	68 - 250 300 2X12V/33Ah/20H 800 750 15 15 490 380 150	69 15/UK 250 300 - 800 750 15 15 490 380 140
Operating weight (kg) 40 60 40	Energy Label Sound pressure level (dB(A)) Cable length (m)/ plug type Brush motor (W) Vacuum motor power (W) Battery type Vacuum (mm H2O) Productivity rate (m²/h) Solution tank (I) Recovery tank (I) Squeegee width (mm) Brush/pad diameter (mm) Brush speed (RPM) Length x width x height (mm)	69 15/UK 250 300 - 800 750 15 15 490 380 140	68 - 250 300 2X12V/33Ah/20H 800 750 15 15 490 380 150 780x415x590	69 15/UK 250 300 - 800 750 15 15 490 380 140 780x415x590
	Energy Label Sound pressure level (dB(A)) Cable length (m)/ plug type Brush motor (W) Vacuum motor power (W) Battery type Vacuum (mm H2O) Productivity rate (m²/h) Solution tank (I) Recovery tank (I) Squeegee width (mm) Brush/pad diameter (mm) Brush speed (RPM) Length x width x height (mm) Battery compartment size (LxWxH) (mm)	69 15/UK 250 300 - 800 750 15 15 490 380 140 780x415x590 -	68 - 250 300 2X12V/33Ah/20H 800 750 15 15 490 380 150 780x415x590 196x130x175	220V 50/60HZ 69 15/UK 250 300 - 800 750 15 15 490 380 140 780x415x590 -



User friendly micro scrubber/dryer perfect for cleaning in narrow areas

Technical specifications	AS380/15B-TR SCRUBBER 24V 50/60HZ	AS380/15C-TR SCRUBBER 230-240V 50/60HZ
Energy Label		
Sound pressure level (dB(A))	65	65
Cable length (m)/ plug type	-	-
Brush motor (W)	250	250
Vacuum motor power (W)	300	300
Battery type	2X12V/33Ah/20H	2X12V/33Ah/20H
Vacuum (mm H2O)	800	800
Productivity rate (m²/h)	750	750
Solution tank (I)	15	15
Recovery tank (I)	15	15
Squeegee width (mm)	490	490
Brush/pad diameter (mm)	380	380
Brush speed (RPM)	150	150
Length x width x height (mm)	780x415x590	780x415x590
Battery compartment size (LxWxH) (mm)	196x130x175	196x130x175
Gross weight (gvw) (kg)	65	65
Operating weight (kg)	60	60

 $[\]bullet$ Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	AS380/15B- EU 15 SCRUBBER 24V 50/60HZ	AS380/15B- UK 15 SCRUBBER 24V 50/60HZ	AS380/15C- EU 15 230-240V 50/60HZ		
and the latest the lat	Battery and Charger							
	KIT CHARGER 24VDC 50-60HZ	VF89023UK	1		•			
- 1	KIT CHARGER 24VDC 50-60HZ	VF89023EU	1	•				
	Viper Accessory							
	BLADE SQUEEGEE FRONT	VF89807	0	•	•	•		
	BLADE SQUEEGEE REAR	VF89808	0	•	•	•		
	BRUSH 15INCH PLASTIC	VF89830	0	•	•	•		
	KIT SQUEEGEE ALUMINUM	VF89821	0	•	•	•		
	PAD DRIVER FOR 15INCSCRUBBER	VF89817	0	0	0	0		



User friendly micro scrubber/dryer perfect for cleaning in narrow areas

 \bullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	AS380/15C- UK 15 230-240V 50/60HZ	AS380/15B- CN 15 SCRUBBER 24V 50/60HZ	AS380/15C- CN 15 220V 50/60HZ
and the latest the lat	Battery and Charger					
	KIT CHARGER 24VDC 50-60HZ	VF89023UK	1			
e H	KIT CHARGER 24VDC 50-60HZ	VF89023EU	1			
	Viper Accessory					
	BLADE SQUEEGEE FRONT	VF89807	0	•	•	•
	BLADE SQUEEGEE REAR	VF89808	0	•	•	•
	BRUSH 15INCH PLASTIC	VF89830	0	•	•	•
	KIT SQUEEGEE ALUMINUM	VF89821	0	•	•	•
	PAD DRIVER FOR 15INCSCRUBBER	VF89817	0	0	0	0

 \bullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	AS380/15B-TR SCRUBBER 24V 50/60HZ	AS380/15C- TR SCRUBBER 230-240V 50/60HZ	
Battery and Charger						
	KIT CHARGER 24VDC 50-60HZ	VF89023UK	1			
- 1	KIT CHARGER 24VDC 50-60HZ	VF89023EU	1	•		
	Viper Accessory					
	BLADE SQUEEGEE FRONT	VF89807	0	•	•	
	BLADE SQUEEGEE REAR	VF89808	0	•	•	
	BRUSH 15INCH PLASTIC	VF89830	0	•	•	
	KIT SQUEEGEE ALUMINUM	VF89821	0	•	•	
	PAD DRIVER FOR 15INCSCRUBBER	VF89817	0	0	0	

