

The fastest way to collect trims in 1,1 kW and 114 liters container

Industrial vacuum for the collection of plastic, paper or textile trims. Its suction power, its features and its size make it the right vacuum to operate in packaging areas.

Model R 154 is equipped with a 1,1 kW threephase motor and a 114 liters container. It mounts a nylon filter, however specific filters for dust extraction are available. The threephase suction unit is placed under the container, the liner is spread out and completely open and all product vacuumed in is neatly compacted on the bottom, optimizing the container capacity.

Small  
No maintenance needed  
Silent  
Easy and quick disposal of waste material  
High capacity  
Quick visual level control: plexiglass port-hole in the lid  
Specific liner filter for fine dust available  
Stainless steel version



Picture shown may not represent model quoted

- Standard equipment

- Standard equipment

Model	R154 V	R154 X	R154 V 5PP
Ref. no.	4031600015	4031600023	4031600077

PRODUCT FEATURES

Filtrační sáček	•	•	•
Filtrační komora z nerez oceli		•	
Ochrana motoru	•	•	•
5-kolíková zásuvka			•
Inspekční okénko	•	•	•
Tlumič			
N°2 vstupy			

Model	R154 X 5PP	R154 V 2ID50 5PP	R154 V S 5PP
Ref. no.	4031600078	4031600100	4031600103

PRODUCT FEATURES

Filtrační sáček	•	•	•
Filtrační komora z nerez oceli	•		
Ochrana motoru	•	•	•
5-kolíková zásuvka	•	•	•
Inspekční okénko	•	•	•



## The fastest way to collect trims in 1,1 kW and 114 liters container

Model	R154 X 5PP	R154 V 2ID50 5PP	R154 V S 5PP
Ref. no.	4031600078	4031600100	4031600103

## PRODUCT FEATURES

Tlumič			•
N°2 vstupy		•	

Technical specifications	R154 V	R154 X	R154 V 5PP
Napětí (V)	400	400	400
Frekvence (HZ)	50	50	50
Ip třída ochrany	55	55	55
Třída izolace	F	F	F
Příkon motoru (KW)	1.1	1.1	1.1
Průtok vzduchu bez hadice (m3/h – l/min)	156 - 2600	156 - 2600	156 - 2600
Max. podtlak(kPa - mbar)	21 - 210	21 - 210	21 - 210
Úroveň hlučnosti	72	72	72
Objem nádoby (L)	114	114	114
Typ hlavního filtru	NYLON MOD.R460	NYLON MOD.R460	NYLON MOD.R460
Plocha hlavního filtru (CM2)	11.500	11.500	11.500
Průměr hrdla (MM)	50	50	50
Délka x šířka x výška (MM)	560x560x1200	560x560x1200	560x560x1200
Hmotnost (KG)	40	40	40

Technical specifications	R154 X 5PP	R154 V 2ID50 5PP	R154 V S 5PP
Napětí (V)	400	400	400
Frekvence (HZ)	50	50	50
Ip třída ochrany	55	55	55
Třída izolace	F	F	F
Příkon motoru (KW)	1.1	1.1	1.1
Průtok vzduchu bez hadice (m3/h – l/min)	156 - 2600	156 - 2600	156 - 2600
Max. podtlak(kPa - mbar)	21 - 210	21 - 210	21 - 210
Úroveň hlučnosti	72	72	72
Objem nádoby (L)	114	114	114
Typ hlavního filtru	NYLON MOD.R460	NYLON MOD.R460	NYLON MOD.R460
Plocha hlavního filtru (CM2)	11.500	11.500	11.500
Průměr hrdla (MM)	50	50	50
Délka x šířka x výška (MM)	560x560x1200	560x560x1200	560x560x1200
Hmotnost (KG)	40	40	40



## The fastest way to collect trims in 1,1 kW and 114 liters container

● Standard equipment, ○ Supplementary accessories, □ Mountable equipment











Accessories		Ref. no.	Min. required	R154 V	R154 X	R154 V 5PP
<b>Hadice k vysavačům</b>						
	50MM ANTI STATIC CUFF	Z7 20325	1	○	○	○
	ANTISTATIC HOSE FDA D40 BY METER	4072400328	1	○	○	○
	ANTISTATIC HOSE FDA D50 BY METER	4072400329	1	○	○	○
	FLOWING PTFE SLEEVE D50	Z7 20326	1	○	○	○
	HANK CONDUCTIVE FLEX HOSE D50 MT.30	4072400234	1	○	○	○
	POL HOSE D50 MT5+SLEEVES	Z7 22366	1	○	○	○
	POL HOSE D50 MT15+SLEEVES	4072200475	1	○	○	○
	SLEEVE D50 PVC	Z7 23023	1	○	○	○
	SLEEVE D50 RUBBER	Z7 20002	1	○	○	○
	SLEEVE D50ANTISTAT.RUBBER COMPONENT ATEX	40000219	1	○	○	○
	TUBE D50 POLYURETHAN MT3+SLEEV	Z7 22298	1	○	○	○
<b>Hadice a spojky</b>						
	SLEEVE FOR ANTISTATIC HOSE FDA D40	4072000358	1	○	○	○




## The fastest way to collect trims in 1,1 kW and 114 liters container

Accessories	Ref. no.	Min. required	R154 V	R154 X	R154 V 5PP
SLEEVE FOR ANTISTATIC HOSE FDA D50	4072000359	1	○	○	○

● Standard equipment, ○ Supplementary accessories, □ Mountable equipment

Accessories	Ref. no.	Min. required	R154 X 5PP	R154 V 2ID50 5PP	R154 V S 5PP
<b>Hadice k vysavačům</b>					
	50MM ANTI STATIC CUFF	Z7 20325	1	○	○
	ANTISTATIC HOSE FDA D40 BY METER	4072400328	1	○	○
	ANTISTATIC HOSE FDA D50 BY METER	4072400329	1	○	○
	FLOWING PTFE SLEEVE D50	Z7 20326	1	○	○
	HANK CONDUCTIVE FLEX HOSE D50 MT.30	4072400234	1	○	○
	POL HOSE D50 MT5+SLEEVES	Z7 22366	1	○	○
	POL HOSE D50 MT15+SLEEVES	4072200475	1	○	○
	SLEEVE D50 PVC	Z7 23023	1	○	○
	SLEEVE D50 RUBBER	Z7 20002	1	○	○
	SLEEVE D50ANTISTAT.RUBBER COMPONENT ATEX	40000219	1	○	○

The fastest way to collect trims in 1,1 kW and 114 liters container

Accessories		Ref. no.	Min. required	R154 X 5PP	R154 V 2ID50 5PP	R154 V S 5PP
	TUBE D50 POLYURETHAN MT3+SLEEV	Z7 22298	1	○	○	○
<b>Hadice a spojky</b>						
	SLEEVE FOR ANTISTATIC HOSE FDA D40	4072000358	1		○	
	SLEEVE FOR ANTISTATIC HOSE FDA D50	4072000359	1		○	